




RoHS
compliant



SPECIFICATIONS

Contact: phosphor bronze
 Contact plating: see ordering information
 Insulator: black glass filled polyester
 UL94V-0

Current rating: 0.75Amps
 Contact resistance: 20mΩ max.
 Insulation resistance: 1000MΩ min. at 100V
 Withstanding Voltage: 300V AC/minute
 Operating temperature: -55°C to +105°C
 Soldering temperature: 260°C ± 5° 5S
 Critical Dimensions: ▼



Ordering Information

FH100020DU1 - 1XX X X X 01

No. of pins
2*3-2*50

Plating Option
 A = Gold Flash
 B = 3U" Gold
 C = 5U" Gold
 E = 15U" Gold
 T = Tin
 Z = Special

Insulator Material
Option
 A = PBT
 B = PAGT
 F = LCP
 Z = Special

Packing Option
 A = Tray
 B = Bag
 C = Tube
 Z = Special

TM-LINK

TM-Link Technology Limited

TITLE: 1.00mm Female Header Single row Dip type

TOLERANCES UNLESS OTHERWISE SPECIFIED:		DRAWN	Robert	DATE:	2012-03-28	DRAWING NO.:	FH100020DU1-1XX-01	
X.XX	±0.25	CHECKED	Jhon	PROJECTION				
X.X	±0.35	APPROVED	Jack	SIZE:	A4	UNIT:	MM	SCALE: 1:1
X.	±0.50					SHEET:	1/1	REV: A